

Impact of Segregation and Density on Asphalt Pavement Performance

Topics of Discussion

- Overview of APT Program
- Impact of Asphalt Mix Segregation on Pavement Performance
- Performance of Asphalt Pavements Constructed Using Different Compaction Levels
- Summary



FDOT's APT Program

- Test Track housed at the State Materials Office
 - 5 Lanes approximately 450 ft. long x 12 ft. wide
 - 2 Lanes 150 ft. long x 12 ft. wide
 - 2 Outdoor Test Pits
- Loading performed using the Heavy Vehicle Simulator (HVS) Mark IV Model.



Research Project Selection

- APT program is integrated with overall research effort
 - Planning, development, and execution of research projects performed on an annual basis
- Research projects solicited from Central and District offices, FHWA, industry, and Florida Universities



Current APT Research


HVS-9 Experiment

1. Asphalt segregation
2. Tack coat residual application rate effect on cracking resistance
3. Asphalt density
4. FC-5 thickness
5. High polymer binder



HVS-9 Experiment

HVS-9 Testing Layout





Environmental Control

- Heater elements attached to HVS test beam
- Maintain asphalt temperature at 120°F
- Asphalt temperature monitored at 2-inches below surface



Heavy Vehicle Simulator

- Loading: 9 kips
- Super Single tire
 - (Goodyear G286 A SS, 425/65R22.5)
- Wheel wander from 0 to 30 inches
- On-board laser profiler system
- Heating system
- 10,000 loaded repetitions per day



Impact of Segregation on Asphalt Pavement Performance



Asphalt Segregation Study

- Quantify the impact of segregation on pavement rutting performance
- Develop/refine methods to quantify segregation using texture measurements (CTM)
- **Finalizing report**



Segregated Test Sections

Asphalt Segregation Study

- 12.5-mm NMAS (Granite)
- PG 76-22 polymer-modified binder
- 450 ft. long x 12 ft. wide test lane

12.5-mm w/ PG 76-22

1.5-inch SP-12.5 w/ PG 76-22
1.5-inch SP-12.5 w/ PG 76-22
1-inch Milled Surface
10.5-inch limerock base
12-inch granular subbase




Test Lane Construction

- Construct the areas with varying severity levels of segregation on test lane
 - Quarter truck loads of asphalt
 - Cycled screed heater on/off
 - Cooler material introduced into paver
 - Material sampling




Construction Methods



Test Track Construction

Temperature Distribution before Compaction




Non Destructive Testing

- Use nondestructive testing methods to quantify the presence of segregation in the field
 - Circular Texture Meter
 - TM2: wide spot laser
- Comparison between segregated and non segregated HVS loading areas
 - Surface texture (MPD)
 - Rutting performance




Additional Non Destructive Testing


- Sand Patch Method
- GPR Data
- Florida Texture Meter



Segregated Pavement Performance



Rutting Performance



Performance of Asphalt Pavements Constructed Using Different Compaction Levels



Asphalt Density

- 12.5 PG 76-22 Asphalt Mixture
- Three densities were targeted
 - 87%, 90%, and 93%
 - $\pm 0.5\%$ Tolerance



Density Test Sections

Asphalt Density Study

- 12.5-mm NMAS (Granite)
- PG 76-22 polymer-modified binder
- 450 ft. long 12 ft. wide test lane

12.5-mm w/ PG 76-22

1.5-inch SP-12.5 w/ PG 76-22
1.5-inch SP-12.5 w/ PG 76-22
1-inch Milled Surface
10.5-inch limerock base
12-inch granular subbase




Establishing Rolling Patterns

Rolling Pattern Results:

Steel Wheel
Vibratory Roller


- Approx. 2200 VPM
- Approx. 4.5 MPH



Florida Department of Transportation

Test Track Construction

Core ID	Core Density (%)	Avg. Core Density (%)	Std. Deviation; (%)	Thickness Top Layer (inches)	Avg. Thickness (inches)	Std. Deviation; (inches)	Location (ft.)
1A	86.4	86.2	0.9	1.5	1.4	0.1	92
2A	85.1			1.3			132
3A	86.1			1.3			60
4A	87.3			1.4			85
5A	90.3	90.2	0.5	1.4	1.4	0.1	208
6A	90.6			1.5			243
7A	89.6			1.4			254
8A	93.1	93.0	0.1	1.3	1.4	0.1	356
9A	92.9			1.4			398
10A	92.9			1.5			400





IDT Tensile Strength

Core ID	Core Density (%)	Avg. Density (%)	Tensile Strength (psi)	Avg. Tensile Strength (psi)	Std. Deviation (psi)
1A	86.4	86.3	95.8	91.3	13.4
2A	85.1		71.3		
4-1B	86.1		98.4		
4-4B	87.6		99.6		
1	89.6	90.3	100.9	119.8	14.8
2	91		132.6		
1A	90		115.1		
2A	90.6		130.4		
6	92.7	92.9	144	151.1	10.4
7	92.9		141.5		
6A	93.1		164.1		
7A	92.9		154.7		



Rutting Performance



Density affects the rutting performance of
12.5 PG 76-22 mixture

In general, rutting performance is
increase with increase density for typical
12.5 PG 76-22 mixtures



Florida Department of Transportation

Segregation Study Summary

- The APT results indicate that segregation negatively impacts the rutting performance of asphalt pavements.
 - The segregated loading areas detected by the current FDOT criteria resulted in 65.9% higher rutting than the non-segregated experienced areas
 - Raveling was observed during testing, but difficult to quantify.



Density Study Summary

- The APT results indicate that asphalt pavement density below 90% negatively impacts rutting performance.
 - 87% density resulted in 29.5% higher rutting than the 93% density test section
 - 87% density resulted in 10.7% higher rutting than the 90% density test section
 - 87% density resulted in 31.2% and 65.9% lower average tensile strength than the 90% and 93% density test sections, respectively.



APT Summary

- APT is a critical component of FDOT's pavement research program
- Key to success is the careful selection of research projects that address critical issues
- Technology transfer is essential

