

Check before each use

Ladder INSPECTION

- ☐ Ladder shall be free of irregularities.
- ☐ Rungs shall be tight in the joint of the side rails.
- ☐ Moving parts shall operate freely without binding.
- ☐ Pulleys wheels, and bearings shall be lubricated.
- ☐ Rungs shall be free of grease and oil.
- ☐ Rope shall not be frayed or badly worn.
- ☐ Nonslip feet shall be in good working order and free of grease.
- ☐ Wood ladders shall be free of splinters, sharp edges, and decay.

**IF ANY ITEMS ARE FAULTY,
REPAIR BEFORE USE.**

Check before each use

Ladder INSPECTION

- ☐ Ladder shall be free of irregularities.
- ☐ Rungs shall be tight in the joint of the side rails.
- ☐ Moving parts shall operate freely without binding.
- ☐ Pulleys wheels, and bearings shall be lubricated.
- ☐ Rungs shall be free of grease and oil.
- ☐ Rope shall not be frayed or badly worn.
- ☐ Nonslip feet shall be in good working order and free of grease.
- ☐ Wood ladders shall be free of splinters, sharp edges, and decay.

**IF ANY ITEMS ARE FAULTY,
REPAIR BEFORE USE.**

Check before each use

Ladder INSPECTION

- ☐ Ladder shall be free of irregularities.
- ☐ Rungs shall be tight in the joint of the side rails.
- ☐ Moving parts shall operate freely without binding.
- ☐ Pulleys wheels, and bearings shall be lubricated.
- ☐ Rungs shall be free of grease and oil.
- ☐ Rope shall not be frayed or badly worn.
- ☐ Nonslip feet shall be in good working order and free of grease.
- ☐ Wood ladders shall be free of splinters, sharp edges, and decay.

**IF ANY ITEMS ARE FAULTY,
REPAIR BEFORE USE.**

Check before each use

Ladder INSPECTION

- ☐ Ladder shall be free of irregularities.
- ☐ Rungs shall be tight in the joint of the side rails.
- ☐ Moving parts shall operate freely without binding.
- ☐ Pulleys wheels, and bearings shall be lubricated.
- ☐ Rungs shall be free of grease and oil.
- ☐ Rope shall not be frayed or badly worn.
- ☐ Nonslip feet shall be in good working order and free of grease.
- ☐ Wood ladders shall be free of splinters, sharp edges, and decay.

**IF ANY ITEMS ARE FAULTY,
REPAIR BEFORE USE.**

Check before each use

Ladder INSPECTION

- ☐ Ladder shall be free of irregularities.
- ☐ Rungs shall be tight in the joint of the side rails.
- ☐ Moving parts shall operate freely without binding.
- ☐ Pulleys wheels, and bearings shall be lubricated.
- ☐ Rungs shall be free of grease and oil.
- ☐ Rope shall not be frayed or badly worn.
- ☐ Nonslip feet shall be in good working order and free of grease.
- ☐ Wood ladders shall be free of splinters, sharp edges, and decay.

**IF ANY ITEMS ARE FAULTY,
REPAIR BEFORE USE.**

Check before each use

Ladder INSPECTION

- ☐ Ladder shall be free of irregularities.
- ☐ Rungs shall be tight in the joint of the side rails.
- ☐ Moving parts shall operate freely without binding.
- ☐ Pulleys wheels, and bearings shall be lubricated.
- ☐ Rungs shall be free of grease and oil.
- ☐ Rope shall not be frayed or badly worn.
- ☐ Nonslip feet shall be in good working order and free of grease.
- ☐ Wood ladders shall be free of splinters, sharp edges, and decay.

**IF ANY ITEMS ARE FAULTY,
REPAIR BEFORE USE.**

Ladder INSPECTION

Equipment ID#

[illegible]

Ladder INSPECTION

Equipment ID#

[illegible]

Ladder INSPECTION

Equipment ID#

[illegible]

Ladder INSPECTION

Equipment ID#

[illegible]

Ladder INSPECTION

Equipment ID#

[illegible]

Ladder INSPECTION

Equipment ID#

[illegible]