

IDUG

2026


Sydney | March 16 - 18

AU Db2 TECH CONFERENCE

**Db2 for z/OS Applications
Empowered with OpenTelemetry**

Sueli Almeida, IBM Silicon Valley Lab

Session Code: C10



Platform:

Db2 for z/OS

- © 2023 International Business Machines Corporation. All rights reserved.
- This document is distributed “as is” without any warranty, either express or implied. In no event shall IBM be liable for any damage arising from the use of this information, including but not limited to, loss of data, business interruption, loss of profit or loss of opportunity.
- Customer examples are presented as illustrations of how those customers have used IBM products and the results they may have achieved. Actual performance, cost, savings or other results in other operating environments may vary.
- Workshops, sessions and associated materials may have been prepared by independent session speakers, and do not necessarily reflect the views of IBM.
- Not all offerings are available in every country in which IBM operates.
- Any statements regarding IBM’s future direction, intent or product plans are subject to change or withdrawal without notice.
- IBM, the IBM logo, and ibm.com are trademarks of International Business Machines Corporation, registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the Web at “Copyright and trademark information” at: www.ibm.com/legal/copytrade.shtml.

Certain comments made in this presentation may be characterized as forward looking under the Private Securities Litigation Reform Act of 1995.

Forward-looking statements are based on the company’s current assumptions regarding future business and financial performance. Those statements by their nature address matters that are uncertain to different degrees and involve a number of factors that could cause actual results to differ materially. Additional information concerning these factors is contained in the Company’s filings with the SEC.


Copies are available from the SEC, from the IBM website, or from IBM Investor Relations.

Any forward-looking statement made during this presentation speaks only as of the date on which it is made. The company assumes no obligation to update or revise any forward-looking statements except as required by law; these charts and the associated remarks and comments are integrally related and are intended to be presented and understood together.

AGENDA



- What is OpenTelemetry?
- Why implement OpenTelemetry
- OpenTelemetry trace for Db2 for z/OS
- Configuration & details
- Next Steps
- Summary & References



- OpenTelemetry is a vendor-agnostic **observability framework**.
 - It consists of a collection of APIs, SDKs, and tools, which can be used to instrument, generate, collect, and export telemetry data to help site reliability engineers (SRE) analyze their software's performance and behavior.
 - Semantic conventions that define a standard naming scheme for common telemetry data types
 - A specification for all components

IBM System Z Statement of Direction

Published on 3rd June 2025



IBM intends to develop capability to support OpenTelemetry (OTel) distributed tracing in IBM CICS Transaction Server for z/OS, IBM Information Management System (IMS), IBM Db2 for z/OS, and IBM MQ for z/OS.


IBM intends that this support will include the native emission of OTel span data from IBM middleware subsystems using emitter capability provided in IBM z/OS and that the output streams will be available for consumption by any observability tooling that supports the OTel standard.

OpenTelemetry Data

- Metrics -> provide runtime measurements of a system.
- Logs -> provide recording of events.
-  Traces -> track the flow of an application through a system, enabling you to observe how applications are behaving.
 - Distributed tracing is a methodology to follow a transaction across multiple software components.

IBM z/OS and its middleware implementation, enables end-to-end tracking of requests across different subsystems, making it easier to identify performance bottlenecks and failures efficiently. [W3C \(World Wide Web Consortium\) Trace Context Specifications](#)

(1) Context Propagation



(2) Export of spans


- Send each span with:
- context: *trace_id, span_id*
 - *parent_id*
 - start- and end timestamp
 - metadata: attributes, events, status, ...

Observability backend - required to make use of collected data.

Trace: single request and its path through a system of services


Span (timespan): represents a unit of work or operation

Tracers are part of the runtime and collect data.







End User



Public Cloud



Private Cloud



Mainframe Services



End-to-end Observability for hybrid applications and underlying infrastructure



Site Reliability Engineer



Application Developer




Systems Programmer

Ensuring the mainframe is at the center of an enterprise-wide observability strategy is essential for maintaining strategic application availability

Adoption of OpenTelemetry standard delivers *insights in context enabling faster detection*, isolation and resolution of operational issues

Understanding the concept of a trace and its spans #IDUGDb2

How the application behaves all the way through



Understanding OTel Span records





Gives you

- Spans aim to provide a way to identify where a problem is in a distributed application.
- Help to identify **which team** needs to be called in to resolve it.
- Spans should **reduce the time** to identify “in which area” when a problem arises in a complex distributed application.

Doesn't give you

- Span data will not generally be sufficient to diagnose the root cause of a problem in most cases
- Conventional diagnostic tools will be needed as now

Distributed Tracing for z/OS System Software – Example



¹ APAR [OA66345](#) (UJ98068 for z/OS 3.1 and UJ98067 for z/OS 3.2)

- [PH67971](#) – Db2 for z/OS OpenTelemetry Distributed Tracing Support
- [PH68073](#) – Db2 for z/OS IMS Attach OpenTelemetry Distributed Tracing Support

Only for inbound workloads with a traceparent from:

- Db2 for z/OS native RESTful services
- JDBC Type-4/Db2 JCC type-4 Client driver ¹
- CICS-Db2 Attachment Facility
- CICS Liberty-JDBC type-2 (RRS AF) ²
- IMS-Db2 Attachment (ESAF)
- IMS-Db2 Java Adapter-JDBC type-2 (RRS AF) ²
- z/OS Connect-Db2 Rest service (HTTP header)

¹ JDBC Type-4 support GA with Db2 Connect 12.1.3 or a special build for Db2 Connect 12.1.2.

² Attachment controlled by CICS or IMS and not JDBC type-2.

- Db2 will emit an OTel span record with basic performance metrics (CPU time and elapsed time) for each unit of work.
- Environments must have IFCID 3 on to report “in Db2” timings
- Environments must be configured to enable the new SMF record 1161 subtype 1

Db2 OTel Distributed Tracing Support (2 | 7)

What's new

SMF Record

- New extended [SMF record type 1161 at subtype 1](#) has been reserved for Db2 OTel span usage
 - A single SMF record may contain multiple spans, however Db2 is writing one SMF record per span.

Messages

- New: [DSNW300I](#) `csect-name DISPLAY OTEL display-otel-output`
[DSNW303I](#) `csect-name OTEL IS ALREADY otel-status.`
 THE command-name OTEL COMMAND IS IGNORED.

Instrumentation

- New: [IFCID 394](#) – OTEL STATISTICS TRACE

Part of CLASS 1 STATS trace and controlled by the STATIME subsystem parameter.

Commands

- Following slides

Enablement switch, after APAR PH67971 applied

- The default behavior when Db2 starts is for the OTel traces to remain stopped.
 - No context propagation or span record emission occurs.
- The Db2 command `-START OTEL` starts OpenTelemetry (OTel) processing

```
>>-START OTEL---+-----+---><
      |                               |
      |           +---YES---+       |
      |           |           |       |
      +---EMIT (-+---NO---+-) -+
```

- EMIT YES -> OTel is started. Context information is propagated, and span records are written. A SMF type 1161, subtype 1 record will be written on commit or abort of an SQL statement (subsystem level).
- EMIT NO -> OTel is started. Context information is propagated but span records are not written.

Enablement switch,
after APAR PH67971
applied

- The Db2 command `-STOP OTEL` stops all Db2 OpenTelemetry (OTel) functions, including propagation of OTel information and writing of extended SMF type 1161, subtype 1 (OTel span)

```
>>-STOP OTEL --<
```

Db2 OTel Distributed Tracing Support (5 | 7)

Enablement switch,
after APAR PH67971
applied

- The Db2 command `-DISPLAY OTEL` displays OpenTelemetry (OTel) status information.

```
>>-DISPLAY OTEL---+-----+---><
                        |           |
                        +---DETAIL---+
```

For example,

```
18.59.15          -db2a dis otel detail
18.59.15 STC00180 DSNW300I  -DB2A DSNWVCM3 DISPLAY OTEL REPORT FOLLOWS:
  STATUS = STARTED
  EMIT   = YES
  RECORDS EMITTED: SUCCESSFUL =          607
                   FAILED     =           0
  TRACE PARENT:   SAMPLING ON =          607
                   VALID      =          607
                   INVALID    =           0
  TRACE STATE:    VALID      =           0
                   TRUNCATED  =           0
                   INVALID    =           0
  LAST STARTED 13:55:38 AUG 22, 2025
  LAST STOPPED 13:55:34 AUG 22, 2025
  DISPLAY OTEL REPORT COMPLETE.
18.59.15 STC00180 DSN9022I  -DB2A DSNWVCM3 '-DIS OTEL' NORMAL COMPLETION
```

The Span record

The OTel specification for a trace span states that it must contain the following elements:

- The span name
- An immutable SpanContext which identifies the span
- A parent span or null
- A spankind
- A start timestamp
- An end timestamp
- Attributes


The Span record, example


```
{
  "serviceName": "DB2A"
  "spanName": "Db2 unit of work",
  "context": {
    "trace_id": "c6b8e70cf380f7c53b5b56ade5e72c88", <--- Requester trace_id
    "span_id": "e11a6a0f06bd10a4" <--- Db2 span_id (STCKF)
    "trace_flags": "01",
  },
  "parent_id": "1d32ee1004345511", <--- Requester span_id
  "span_kind": "SERVER", <--- Db2 generates span kind "SERVER"
  "start_time": "2024-06-03 11:58:22.209458162 +0000 UTC",
  "end_time": "2024-06-03 11:58:23.337895675 +0000 UTC",
  "status_code": "STATUS_CODE_OK",
  "attributes": {
    "db.system.name": "ibm.db2",
    "db.ibm.db2.version": "V13R1M500", <--- Db2 version and function level
    "db.ibm.db2.group.name": "DSNCAT", <--- DS only; DS group name
    "db.ibm.db2.member.name": "DB2A", <--- DS only; DS member name
    "db.ibm.db2.subsystem.name": "DB2A", <--- Db2 subsystem name
    "db.ibm.db2.location": "STLEC1", <--- Db2 location name|
    "db.ibm.db2.luwid": "G93D8ED4.F28A.E11A6A0C5FB0.0004", <--- Db2 LUWID
    "db.ibm.db2.connection.type": "DIST", <--- Connection type string
    "db.ibm.db2.connection.id": "SERVER", <--- Connection ID string
    "db.ibm.db2.correlation.id": "::FFFF:9.61.142.212.62090.E11A6A0C5FB0", <--- Correlation ID
    "db.ibm.db2.planname": "DISTSERV",
    "db.ibm.db2.et": 1930, <--- "In Db2" Elapsed time in microseconds
    "db.ibm.db2.cpu.gp": 1784, <--- "In Db2" GP CPU time in microseconds
    "db.ibm.db2.cpu.ziip": 0, <--- "In Db2" zIIP CPU time in microseconds
  },
}
```

An end-to-end example

Tn – trace ID
Sn – span ID
Pn – parent ID

OTel root span creation 





JAEGER UI Search Compare System Architecture Monitor Q Lookup by Trace ID... About Jaeger

← CICS TG Java SDK: CLIENT JAVA REQUEST: a6a2167 Find... Trace Timeline Archive Trace

Trace Start **August 22 2025, 12:56:14.363** | Duration **740.18ms** | Services **5** | Depth **6** | Total Spans **6**

Service & Operation	0µs	185.05ms	370.09ms	555.14ms	740.18ms
<ul style="list-style-type: none"> CICS TG Java SDK CLIENT JAVA REQUEST: <ul style="list-style-type: none"> CICS TG Java SDK ECI Java Request <ul style="list-style-type: none"> CICS Transaction Gateway Call CICS <ul style="list-style-type: none"> ZZD1AAAA CICS transaction MGIA <ul style="list-style-type: none"> ZZD1BBAB CICS transaction MGIA <ul style="list-style-type: none"> DLUB Db2 unit of work 					
Db2 unit of work Service: DLUB Duration: 86µs Start Time: 126.22ms <ul style="list-style-type: none"> Tags: db.ibm.db2.connection.id = ZZD1BBAB db.ibm.db2.connection.type = SASS db.ibm.db2.correlation.id = POOLMUAC0002 db.ibm.db2.cpu.gp = 50 db.ibm.db2.cpu.ziip = 0 db... Process: telemetry.sdk.language = java telemetry.sdk.name = opentelemetry telemetry.sdk.version = 1.52.0 SpanID: e15ff67b1ab7f368					

[Search](#)
[Upload](#)

Service (19)

Operation (1)


Tags ⓘ

Lookback

Max Duration
Min Duration

Limit Results

[Find Traces](#)



20 Traces

 Sort:

Compare traces by selecting result items

ZZD1AAAA: CICS transaction CWXN 9951636 23.62ms

DLUA (1)
 ZZD1AAAA (3)
 ZZD1DAAA (1)

 Today | 12:01:36 pm
 a few seconds ago

ZZD1AAAA: CICS transaction CWXN 0989970 1.54ms

DLUA (1)
 ZZD1AAAA (3)

 Today | 12:01:36 pm
 a few seconds ago

ZZD1AAAA: CICS transaction CWXN 9104390 2.63ms

DLUA (1)
 ZZD1AAAA (3)
 ZZD1DAAA (1)

 Today | 12:01:36 pm
 a few seconds ago

ZZD1AAAA: CICS transaction CWXN 5375642 2.38ms

DLUA (1)
 ZZD1AAAA (3)
 ZZD1DAAA (1)

 Today | 12:01:36 pm

Search Upload

Service (19)

DLUB

Operation (1)

all

Tags ?

http.status_code=200 error=true

Lookback

Last Hour

Max Duration

e.g. 1.2s, 100ms, 500us


Min Duration

e.g. 1.2s, 100ms, 500us

Limit Results

20

Find Traces



20 Traces

Sort: Most Recent

Download Results

Deep Dependency Graph

Compare traces by selecting result items

- ZZD1AAAA: CICS transaction CWXN** 7050282 4.72ms
 12 Spans DLUB (1) ZOSCNCT-ZCCA_ZZD1ZABD (5) ZZD1AAAA (3) ZZD1BBAD (2) ZZD1DAAA (1) Today 12:01:46 pm a few seconds ago
- ZZD1AAAA: CICS transaction CWXN** 8264590 4.3ms
 12 Spans DLUB (1) ZOSCNCT-ZCCA_ZZD1ZABB (5) ZZD1AAAA (3) ZZD1BBAB (2) ZZD1DAAA (1) Today 12:01:46 pm a few seconds ago
- ZZD1AAAA: CICS transaction CWXN** 7597171 3.01ms
 6 Spans DLUB (1) ZZD1AAAA (3) ZZD1BBAB (1) ZZD1DAAA (1) Today 12:01:46 pm a few seconds ago
- ZZD1AAAA: CICS transaction CWXN** 2660098 2.37ms
 6 Spans DLUB (1) ZZD1AAAA (3) ZZD1BBAB (1) ZZD1DAAA (1) Today 12:01:46 pm

✓ BANK2TOR CICS transaction PAYB

✓ BANK2AOR CICS transaction PAYM


DB2C Db2 unit of work

Db2 unit of work

Tags


db.ibm.db2.connection.id	BANK2AOR
db.ibm.db2.connection.type	SASS
db.ibm.db2.correlation.id	POOLPAYM0001
db.ibm.db2.cpu.gp	322
db.ibm.db2.cpu.zip	0
db.ibm.db2.et	956
db.ibm.db2.group.name	DSNV130T
db.ibm.db2.location	DSNV130T
db.ibm.db2.luwid	DSNV130T.CFD1.E1447492999B.0001
db.ibm.db2.member.name	DB2C
db.ibm.db2.planname	AOR2
db.ibm.db2.subsystem.name	DB2C
db.ibm.db2.version	V13R1M501
db.system.name	ibm.db2
otel.scope.name	z/OS OTel
otel.scope.version	1.4.0-beta25
span.kind	server

Graphical view example – Transaction Flow



CPU overview

CPU data from z16 model 7xx



z/OS

zIIP eligible

Distributed

Note: measurements taken at pre-GA time

Next Steps



- Add support for OTel Trace Context Propagation for Outbound DRDA connections to a remote Db2 for z/OS Server
- Enhance Db2 OTel Trace Span record
 - Adding the reporting of IDAA offload activity that occurred during the Db2 unit of work represented by a Db2 OTel Trace Span record
 - User ID for incoming DDF traffic
- Add support for JCC type-2 driver
- Add Support for ODBC/CLI driver (CLI, .Net, Python)

Summary



- What is OpenTelemetry (OTel)
- The importance to adopt OpenTelemetry on System Z
- The System Z strategy
- OTel concepts and terms
- An end-to-end example of tracing a hybrid application
- Db2 OTel distributed tracing implementation
 - Prerequisites
 - Enablement switches
 - What is new with this support
 - Examples

References

- [Db2 for z/OS Distributed Tracing and OpenTelemetry support](#)
- Blogs:
 - [OpenTelemetry Support in Db2 for z/OS](#)
 - [Practical guide to OpenTelemetry tracing for Java programs connecting to Db2 for z/OS – Part 1](#)

- [W3C Trace Context specification](#)
- [General OTel overview](#)
- [Open Telemetry specifications](#)
- [Semantic conventions for SQL databases client operations](#)
- [Semantic conventions for database client spans](#)
- [OTel SDK exporters \(span\)](#)
- [Semantic conventions for attributes](#)
- [OTEL semantic convention attribute registry](#)

- [OpenTelemetry tracing with IBM MQ on z/OS](#)
- [CICS and OpenTelemetry](#)
- [IMS and OpenTelemetry](#)
- [z/OS Connect and OpenTelemetry](#)

IDUG

2026

Sydney | March 16 - 18

AU Db2 TECH CONFERENCE

**Db2 for z/OS Applications
Empowered with OpenTelemetry**

Sueli Almeida, IBM Silicon Valley Lab

Contact: sueli@us.ibm.com

Session Code: C10



Platform:

Db2 for z/OS

An aerial view of Sydney, Australia, at dusk. The Sydney Harbour Bridge is prominent on the left, spanning the water. The city skyline is visible in the background with many skyscrapers lit up. In the foreground, there are many sailboats in the harbor. A blue bar is at the bottom of the image.

IDUG

2026 Australia **Db2** Tech Conference