

HOLLWAY PRESENTATION

Sink options for Winter – and Beyond

November 19, 2020 - 3:00-4:25pm

By Derek Pauling



- OSHA Standards review for hand washing
- ▶ Winter sink option 1 Creating a sink house w/ existing equipment
- ▶ Winter sink option 2 Hot/Cold water sink installed in a job trailer
- ▶ Winter sink option 3 Sink Trailer inside of a warehouse
- Winter additive options to safely keep fresh water from freezing
- Service considerations for renting and servicing sinks in the winter and beyond
- Questions

OUTLINE - SINK OPTIONS FOR WINTER AND BEYOND

Standard	Covers	Toilets Required	Hand Wash Required
ANNI/PNAL/AS-	Anywhere non- sewered sanitation is needed	1 unit per 10 workers if serviced once a week	1 station per 10 toilets
OSHA <u>1926.51</u>	Construction sites	1 unit per 20 workers which must be maintained in a sanitary condition	Each lavatory shall be provided with hot and cold running water or tepid running water, hand soap or similar cleansing products, and paper or cloth towels or a blow dryer
OSHA <u>1915.88</u>	Shipyards	Units on a scale beginning with a 1:15 ratio	One unit at or adjacent to each toilet equipped as above
OSHA <u>1918.95</u>	FOLIGINAL MOLVELS	No specific number; the standard just states toilet facilities must be "sufficient for the sanitary requirements of employees shall be readily accessible at the worksite"	No specific number; the standard just states, washing facilities must be "sufficient for the sanitary requirements of employees shall be readily accessible at the worksite" and equipped as above

OSHA STANDARDS HAVE ALWAYS REQUIRED HAND WASHING FACILITIES

Both of these sinks can be placed in a "sink house"



LARGE CAPACITY 2 – STATION HAND WASH STATION

30.25"W x 34"D x 47.75"H 120 pounds empty 500 pounds full 45 gallon grey water capacity 45 gallons fresh water capacity







2-Station Sink Standard Capacity

19"W x 30"D x 59"H
65 pounds empty
215 pounds full
22 gallon grey water capacity
22 gallons fresh water capacity







Basic types of hand wash sinks and specifications







HOT/COLD POTABLE WATER SINGLE HAND WASH STATION

>28"W x 20.5"D x 39"H 105 pounds empty 122 pounds full

110V, 15Amps power requirements

Requires:

Garden hose connection OR 5 gallon fresh water bottles



▶ Basic types of hand wash sinks and specifications

16ft. 12 STATION SINK TRAILER



ENGTH: 16', 21' W/ TONGU

WIDTH: 8'6" HEIGHT: 7'11"


FRESH: 525 GALLONS
WASTE: 525 GALLONS
CAPACITY: 4,000 USES
WEIGHT: 4,000 LBS. (DRY)
WEIGHT: 8,200 LBS. (WET)
TANDEM AXLE: (2) 5,200 LBS.

TANKLESS WATER HEATER: (2) 60,000 BTU STAINLESS STEEL DIVIDERS: 24" X 30"

Sink trailer can be placed inside of a warehouse or heated tent,

Winter additives for use in hand wash sinks

Option 1 – Nev-r-freeze



Option 2 – EZ Flow Freshwater Anti-Freezing Concentrate

MIXING DIRECTIONS

26F 10% EZ Flow - 90% Water

18F 20% EZ Flow - 80% Water

7F 30% EZ Flow - 70% Water

-8F 40% EZ Flow - 60% Water

-29F 50% EZ Flow - 50% Water

THESE SOLUTIONS ARE AVAILABLE AND WILL NOT FREEZE AT THE APPROPRIATE MIX LEVELS AND ARE COMPLETELY SAFE TO WASH YOUR HANDS WITH

SERVICE TRUCK WITH HEATED TANK AND COMPARTMENTS







Heated & Insulated water pump box



Heated and insulated fill hose box

Each time you service the sink in the field be sure to add chlorine tablets to the tank as you re-fill fresh water. Remember when pumping the grey water to use a different WAND and HOSE from what you use on the toilet

CLEAN WATER – CLEAN PUMPING









Questions?