

Mat Defects – Fix it !



Presented by: Todd Mansell, Caterpillar



1

Role of the Paver



- To meet specifications for grade, texture & smoothness



Caterpillar: Confidential Green



2

What is a Mat Defect?

Equipment setup or operational procedures that result in a non-uniform mat:

- Appearance - lines in the mat
- Non-uniform mat texture – surface appearance only
- Segregation – throughout depth – affects density, possibly smoothness
- Bumps & dips in the mat – smoothness, long-term performance
- Cracking, checking, potholes – long-term performance
- Wrong grade/slope, drainage – safety, performance
- What else??

Caterpillar: Confidential Green



3

What Causes Mat Defects?

- Grade conditions – spills, trucks, preparation
- Loading & unloading trucks - plant
- Paver & screed
 - setup & maintenance
 - operation
- Poor take-offs at transverse joint
- Handwork, raking
- Paving too fast
- Roller settings & operation

Caterpillar: Confidential Green



4

What Do Mat Defects Look Like?



Caterpillar: Confidential Green



5

What Happened??



Caterpillar: Confidential Green



6

Grade Conditions: Spills on the Grade




- Potholes
- Density problem
- Smoothness problem

Caterpillar: Confidential Green



7

Spills on grade are BIG mistakes!



Caterpillar: Confidential Green



8

Grade Conditions: Mix on the Grade




- Mix left by pickup machine



Caterpillar: Confidential Green



9



10

Grade Conditions: Spills



- Continuous spill out of hopper
- May be caused by truck bed too short
- May be caused by damaged / missing flashing
- Often run over the paver undercarriage

Caterpillar: Confidential Green



11

Grade Conditions: Spills




- Pile compacted by truck or paver
- May be completely covered by mat depending on thickness

Caterpillar: Confidential Green



12

Grade Conditions – Spills



Cold Compacted Material

- Small compacted pile usually not visible in mat surface
- Thin layer of fresh mix for compaction
- Uneven compaction
- Bump
- Fractured aggregates

Caterpillar: Confidential Green



13

The result...Potholes!



Caterpillar: Confidential Green



14

The result...dragging rock!



Caterpillar: Confidential Green



- Premature raveling
- Bumps after compaction

15

Grade Conditions – Spills



Caterpillar: Confidential Green



- Caused by folding hopper wings too soon
- Caused by damaged or missing flashing
- Becomes cooler mix covered by mat
- What should you do?

16

Banging out truck beds!



What should you do?



Caterpillar: Confidential Green



17

Direct truck to a clean out area



Mix can be recycled at end of the day



Clean-out Area

Caterpillar: Confidential Green



18

Grade Conditions: Trucking



- Trucking has big impact
- Apply light brake pressure
- Too much brake pressure is also a problem
- Do we train our drivers?

Caterpillar: Confidential Green



19

Grade Conditions – Inspect!



- Existing grade conditions often result in mat defects
 - Soft base
 - High spots / low spots
 - Torn up by trucks
- What do we do?

Caterpillar: Confidential Green





20

Segregation is a Mat Defect

1. Physical – Lack of uniformity of aggregates in-place mat
2. Thermal – non-uniform distribution of temperature



Caterpillar: Confidential Green



21

What does segregation look like?



Caterpillar: Confidential Green



CAT

22

Mat Texture is not Segregation



Caterpillar: Confidential Green

- Visual appearance of the surface
- Not the same as aggregate segregation
- Affected by many factors
- Goal is uniformity from edge to edge




23

How Do We Identify Segregation?



Caterpillar: Confidential Green

- Visual
- Often subjective
- Some specs have procedures to quantify segregation



Photograph © Road Segregation



24

Identifying Segregation: 3 Patterns



To eliminate segregation, we must identify the pattern to find the source


1. Repeat, pattern patch
2. Continuous stripes
3. Random patch or stripe

Caterpillar: Confidential Green



25

Segregation areas around the Paver



- Feed system
 - Conveyors
 - Augers
 - Feed sensors
- Hopper

Caterpillar: Confidential Green



26

Segregation – Hopper Management



Caterpillar: Confidential Green

- Flashing in good condition
- Hopper mix level covers slat conveyors and tunnels



27

Segregation – End-of-Load



Caterpillar: Confidential Green

- Usually equally spaced
- Often chevron shape
- Most common when aggregates are 3/4" or larger



CAT

28

End-of-load – Three Drops at Plant



- Troubleshoot truck loading
- First drop at front
- Second drop at rear
- Third drop in center
- Significant reduction in material roll-down
- **Very important when paving with large stone mixes**

Caterpillar: Confidential Green



29

End-of-load Segregation – Truck Bed



- Pockets of large aggregates at ends and sides of truck beds
- Keep bed raised to minimize additional rolldown

Caterpillar: Confidential Green



30

End-of-load – Segregation in Hopper



Caterpillar: Confidential Green

31

End-of-load – Segregation in Hopper



Caterpillar: Confidential Green

- Large aggregate accumulates at sides of hopper
- Prohibit folding hopper wings
- Keep conveyors full during truck exchange
- Shovel out hopper sides occasionally

CAT

32

End-of-Load: Keep Tunnels Covered



Caterpillar: Confidential Green

CAT

33

End-of-load Segregation: MTV Remixing



- Some MTVs have remixing capability
- Surge capacity with mixing augers or paddles
- Blend segregated mix prior to discharge into hopper or insert
- Specified on some projects

Caterpillar: Confidential Green

CAT

34

End-of-Load Segregation: MTV Blending



Caterpillar: Confidential Green

- Pattern segregation minimized
- Highly recommended for large stone mixes and SMA



35

End-of-Load – Cold Chunks



Caterpillar: Confidential Green

- Cold weather and long hauls may cause cold chunks
- MTV will re-mix and break up chunks
- Lower flow gates, if equipped
- Cover loads
- Insulated beds



36

End-of-Load – Cold Chunks



Caterpillar: Confidential Green

- Lots of hand work to remove chunks and repair the mat
- Consider putting laborers at each end of the auger chamber
- May be able to shovel out chunks before going under screed



37

Managing Segregation – Truck Exchange



Caterpillar: Confidential Green

Four step procedure

1. Release truck
2. Continue paving
3. Pave & fold wings
4. Stop quickly



38

Managing Segregation – Truck Exchange



39

STEP 1: Release Truck



- Follow four step routine
- Step one - release truck as soon as bed is empty
- Truck lowers bed and pulls away
- Continue paving at normal speed

Caterpillar: Confidential Green



40

STEP 2: Continue Paving



- Step two - continue paving as truck pulls away
- Pave until level of mix permits cycling hopper wings without spillage—*if allowed*
- Next truck getting position

Caterpillar: Confidential Green



41

STEP 3: Pave & Fold Hopper Wings



- Step three - continue paving at normal speed
- Slowly fold hopper wings combining mix from sides with mix in middle

Caterpillar: Confidential Green



42

Cycling Hopper Wings



- Cycling hopper wings may be prohibited when laying large stone mixes
- Large stone rolls to sides of hopper
- Folding wings contributes to end-of-load segregation
- Shovel out sides of hopper periodically

Caterpillar: Confidential Green



43

STEP 4: Stop Paver Quickly



- Step four - stop paver and lower hopper wings
- Mix in hopper covers deck and conveyors
- Mix in hopper will be covered by next load

Caterpillar: Confidential Green



44

Truck Raises Bed Quickly, but Smoothly



Caterpillar: Confidential Green



45

Trucks Bumping the Paver



Caterpillar: Confidential Green

46

Pave & Fold Hopper Wings



- Slowly fold hopper wings combining mix from sides with mix in middle
- Don't spill out front
- Flashing in good shape

Caterpillar: Confidential Green



47

Mat Defects Related to Truck Exchange



Stop short of paver



Bad hopper flashing



Truck rolled away



Loading at plant



Clean Out Area



Gaps in windrows

Caterpillar: Confidential Green



48

Random Patch



Caterpillar: Confidential Green

- Appears in the mat without pattern
- Comes and goes
- Difficult to pin down
- Usually paver operation related and with large aggregate mixes



49

Random Patch – Hopper / Insert Level



Caterpillar: Confidential Green

- Check level of mix in hopper or insert
- Large aggregates roll to the sides when dropped
Keep insert at least half full with large stone mixes



50

Random Patch – Insert Low



Caterpillar: Confidential Green

- Large aggregates accumulate on sides as level drops
- Center empties first
- Segregated, large aggregates empty last
- Stop paving
- Wait for more mix
- Do not empty hopper / insert
- Do not empty MTV




51

Random Patch – Drop Height



Caterpillar: Confidential Green

- Discharge into hopper or insert from low height
- Low height means less velocity
- Aggregates do not roll as much
- Segregation reduced



52

Feed System Segregation





Caterpillar: Confidential Green

- Conveyor speed too fast
- **WHY?**
- Do we get density here? Smoothness?



53

Random Patch – Feeder Erratic



Caterpillar: Confidential Green

- Feeder system runs erratic, On / Off, fast slow
- Large aggregates separate and roll into dead areas
- Under center chain case, auger bearing cases, tractor mainframe break
- Patches move around, appear and disappear, **as feeder system changes**
- Results from inconsistent paving speeds, too



54

Random Patch – Sensor Position



Caterpillar: Confidential Green

- Important troubleshooting step
- Re-aim sonic feeder sensor
- Major factor in feeder system problems



55

Continuous Stripe



Caterpillar: Confidential Green

- Easily confused with texture stripes
- Open texture appearance
- Presence of mostly large aggregate in the stripe
- Almost always caused by feeder system operation or set-up
- Follow the stripe to its source at the paver



56

Continuous Stripe – Damaged Strike-off ?



Caterpillar: Confidential Green

- Hitting water valves, manholes, etc.



CAT

57

Continuous Stripe - Centerline



Caterpillar: Confidential Green

- Centerline stripe
 - conveyor speed too high
 - auger speed too low
 - anti-segregation kit missing


CAT

58

Centerline Stripe - Centerline



- Lead crown installed?
- Worn deflector plate(s)
- Reversing auger(s)



Caterpillar: Confidential Green

59

Keep deflector plates clean




- Wear item to be replaced
- Centerline streak



Caterpillar: Confidential Green

60

Reversing Augers



Caterpillar: Confidential Green

- Check condition of reversing augers
- Consider installing one “pull-type” reversing auger
- One auger segment pushing mix and one pulling mix will eliminate stagnant area

61

Intermittent Stripe



Caterpillar: Confidential Green

- Intermittent stripes traced to feeder system
- Left auger erratic
- Head of material erratic
- Left side feeder system running at maximum speed
- Throwing aggregate to create stripe
- Sensor too far from target

CAT

62

Intermittent Stripe




Caterpillar: Confidential Green

- Feeder system catches up to the demand
- Extension over-filled
- Auger shuts off
- Stripe stops
- Head of material recedes
- Cycle starts again
- **Solutions:**
 - more auger / tunnel ext.
 - re-aim sensor
 - adjust mix height dial




63

Aiming Sonic Feed Sensors



Caterpillar: Confidential Green

- Mechanical or sonic
- Control level of material
- Position Sensor 18" from end of augers



64

Auger Speed 20 – 40 rpm




- 2s per revolution
- Auger speed too high or too low can cause stripes in the mat

Caterpillar: Confidential Green



65

Continuous Stripes - Conveyor Speed



Caterpillar: Confidential Green



66

Paver Speed – Texture & Segregation

- Goal is non-stop paving
- Set to match mix delivery
- Balance with rollers
- **Quick starts/stops**
- 60 fpm maximum



Caterpillar: Confidential Green



67

Changes in Paver Speed



Caterpillar: Confidential Green

- Changes in paver speed may require feeder system adjustments
- Too often, paver speed changes, but feeder system ratio dials or flow gates are not adjusted to match new paver speed




CAT

68

Random Patches - Quick Starts & Stops



- Feed system engages when paver leaves neutral
- Feed starts, paver isn't moving
- Amplifies end-of-load segregation



Caterpillar: Confidential Green



69

Continuous Paving



- MTVs can help
 - Non-stop between trucks
- Approximately 15% improved smoothness

Caterpillar: Confidential Green




70

Mat Texture – Screed Condition



Caterpillar: Confidential Green

- Condition of screed affects mat texture
- Texture striping indicates non-uniform pressure
- Check screed flatness



71

Paver Stops & Starts...Screed Settlement




Caterpillar: Confidential Green

- Smoothness issue
 - Will it roll out?
- Non-uniform compaction
 - Temperature differentials
- Short stops normal
- Stops > 6 min = bump
- Rolls out, no problem

CAT

72

Paver Stops - density & smoothness



Caterpillar: Confidential Green



73

Mat Texture – Auger Shadows



- Texture stripes appear directly behind the augers
- Especially common with large aggregates
- Raise augers until mat is tight and uniform




Caterpillar: Confidential Green



74

Angle of Attack



- Angle of attack is the relationship between the nose of the screed & the grade
- 1/8" to 1/4" uses all screed plate
- Established at start of each pull



CAT

75

Mat Texture – Angle of Attack




- Correct angle of attack
- Uniform pressure exerted
- Uniform tight texture
- Slightly low angle of attack
- Different pressure
- Slightly open texture

Caterpillar: Confidential Green

CAT

76

Mat Texture – Angle of Attack



- Correct angle of attack
- Flat angle of attack
- adjustment needed
- Slough box
- no adjustment possible

Caterpillar: Confidential Green



77

Mat Texture – Angle of Attack Corrected



- Surface texture uniform after adjusting angle of attack
- Open texture behind strike-off slough box unavoidable

Caterpillar: Confidential Green

78

Auger Extensions & Tunnels



- Fixed width paving
- Variable width paving
- Front-mount screeds
- Rear-mount screeds




Caterpillar: Confidential Green

79



Front-mount and Rear-mount Screeds

Front-mount



Caterpillar: Confidential Green

Rear-mount



80

Front-mount Screeds



18" with front-mount



81

Rear-mount Screeds




36" with rear-mount



Caterpillar: Confidential Green

82

Always Extend Tunnel in front of Augers



Caterpillar: Confidential Green

83

Continuous Stripe



Caterpillar: Confidential Green

- Improperly positioned feed sensor
- Crew is overloading
- Mix is 'rolling' around mainframe, creating stripe in the mat
- Need more auger extensions
- Need mainframe (tunnel) extensions

84

Continuous Stripe



Caterpillar: Confidential Green

- Left extension out 2'
- Mix rolling around mainframe break
- Left extension was retracted from wider width
- Mix trapped between end gate and main screed
- Need to shovel out "dead" area



85

Continuous Stripe - Rear Mount Screed



Caterpillar: Confidential Green

- "Dead zone" of cold, stagnant mix can leave stripes
- How do we fix this?



86

Continuous Stripe



Caterpillar: Confidential Green

- Wide-width paving kit for 6' extension
- Augers within 2' of end gate
- Augers covered by mainframe extension
- No stripe in mat



87

Mat Texture – Screed Extension Lines



Caterpillar: Confidential Green

- Continuous line means height mismatch between main screed and extension
- Lined up with outer edge of main screed, extension too high
- Lower extension to erase line



88

Mat Texture – Screed Extension Lines



- Lined up with inner edge of screed extension, extension too low
- Raise extension to erase line
- If line re-appears behind outer edge of main screed, use extension slope switch to erase line

Caterpillar: Confidential Green



89

Handwork: Shoveling, luting, raking



- Transverse joints
- Longitudinal joints
- Manholes, valves, etc.



Caterpillar: Confidential Green





90

Don't Rake Longitudinal Joints!



INCORRECT SQUARE JOINT -- END GATE UP

CORRECT SQUARE JOINT -- END GATE DOWN



Caterpillar: Confidential Green

91

“Light Bumping” if Necessary



- May be necessary with ¾” or larger stone mixes
- Where slight height mis-match when joint matching using ski



No raking! Nice job guys 😊

Caterpillar: Confidential Green



92

Mat Defects Taking Off



PAVING BY THE NUMBERS

1. Heat the screed
2. Set the tow points
3. Set paving width
4. Set crown
5. Set extender height
6. Set extender slope
7. Lower screed and remove slack
8. Null the screed
9. Position end gates
10. Set auger height
11. Position feeder sensors
12. Set feeder controls
13. Fill auger chamber/place in auto
14. Set accessory functions
15. Pull off starting reference



GE301403-01
(Replaces GE301403-00)

© Caterpillar 2014
All rights reserved.

Caterpillar: Confidential Green



93

Cold Screed



Heating element burned out?



Caterpillar: Confidential Green



94

Is this a good place to start?



Caterpillar: Confidential Green

95

What's wrong with this take-off ?



Caterpillar: Confidential Green

96

No starter boards!

What's going to happen?



Build a Pad or use Starter Boards



Caterpillar: Confidential Green

- Support full length of screed & extensions
- 3 to 4 feet long boards
- Based on uncompact mat thickness (1/4" per 1")



97

Measure Height of Starting Joint




Caterpillar: Confidential Green

- Calculate thickness of starter boards
- General rule vibratory screed:
1/4" compaction per 1" loose depth
- Example: Place 2-1/2" loose to end up with 2" after rolling




98


Boards must support main & extenders



Full Support Main & Extenders







Screed will drop or 'nose over'

Caterpillar: Confidential Green 

99

Mat Defects: Rollers



Caterpillar: Confidential Green 


100

Managing Head of Material @ 1/2 Auger



85-95% of all mat defects are related to head of material!!

1. Ratio dials (or flow gates)
2. Auger height
3. Feed sensor position
4. Auger speed




CAT

Caterpillar: Confidential Green

101

Head of Material @ 1/2 auger



CAT


Caterpillar: Confidential Green

102

Consistency & Communication are the Keys to Success!

- Do the fundamentals right
- Avoid BIG mistakes
- Quality costs nothing

We use the same equipment - we just need to *plan ahead* and *communicate*!



Caterpillar: Confidential Green



103

Mat Defects Troubleshooting Guide

Problem	Causes																			
	Fluctuating Load of Material	Excessive Play in Screed Adjustment Linkages	Overcrowding Linkages	You Must Load Crown in Screed	You Must Load Crown in Screed	Frontal Screed Overload	Frontal Screed Overload	Screed Paves from Left to Right	Screed Paves from Right to Left	Screed Paves from Left to Right	Screed Paves from Right to Left	Roller Screed Worn at or Between Rollers	Rolling Mop or Empty Caster for Inaccuracy	Rolling Mop or Empty Caster for Inaccuracy	Screed Control Valve Backed for Inaccuracy	Grade Control Valve Backed for Inaccuracy	Grade Control Valve Backed for Inaccuracy	Grade Control Valve Backed for Inaccuracy	Grade Control Valve Backed for Inaccuracy	Grade Control Valve Backed for Inaccuracy
Wavy Surface – Short Waves (Ripples)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Wavy Surface – Long Waves	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Tearing of Mat – Full Width		✓																		
Tearing of Mat – Center Streak			✓																	
Tearing of Mat – Outside Streaks				✓																
Mat Texture – Nonuniform	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Screed Marks																				
Screed Not Responding to Correction																				
Auger Shadows		✓																		
Poor Precompaction		✓																		
Poor Longitudinal Joint	✓	✓		✓																
Poor Transverse Joint		✓																		
Transverse Cracking (Checking)																				
Mat Shoving Under Roller																				
Roller Marks																				
Poor Mix Compaction																				

Procedure for Using Table
 1. Find problem above.
 2. Checks indicate causes related to the paver.
 X's indicate other problems to be investigated.

NOTE: Many times a problem can be caused by more than one item, therefore, it is important that each cause listed be eliminated to assure solving the problem.

© Caterpillar 2019 All rights reserved.

104

Thank-you for your attention! Questions?



© 2025 Caterpillar. All Rights Reserved

Materials and specifications are subject to change without notice.

Featured machines in photography may include additional equipment for special applications.

CAT, CATERPILLAR, BUILT FOR IT, their respective logos, "Caterpillar Yellow," and the POWER EDGE trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.



Caterpillar: Confidential Green